

Walk-in Coolers and Freezers from Harford Duracool, LLC



Harford



Harford Modular Walk-Ins General Specifications

- 4" poured-in-place R28 urethane insulation.
- UL 25 low flame spread panel ratings.
- FACTORY MUTUAL APPROVED.
- Tongue and groove edges with foamed-in-place gaskets.
- Cam action panel locks for fast and easy installation.
- NSF approved with floor (.080 textured aluminum) and without floor (coved vinyl screed).
- Metal finishes include: 20 or 22 gauge stainless steel; .032/.040 stucco aluminum, .040 smooth or stucco white aluminum, 24 gauge white stucco galvanized, FRP and popular 26 gauge stucco galvalume from stock.
- Variety of standard and custom-made sizes for every requirement – both indoor and outdoor.
- Numerous optional accessories available.

Harford Door Sections General Specifications

- UL listed for electrical safety.
- 36" standard width opening with infitting flush door.
- Two heavy-duty, self-closing, strap-type hinges.
- Unbreakable pull handle with cylinder lock and inside release to prevent entrapment.
- Positive door closer, magnetic gaskets.
- The heavy duty FRP pultrusion provides a thermal barrier that eliminates a costly second heater circuit required on other low temperature doors. (Consider the energy savings of that!)
- Interior shatter-proof light; exterior switch with pilot.
- Large, readily visible exterior dial thermometer.
- Numerous sizes and optional accessories available.



High-Quality Walk-ins

Walk-in Coolers & Freezers • Refrigeration Systems • Refrigerated Warehouses

HARFORD DURACOOOL LLC 2129 Pulaski Hwy, P.O. Box 1026, Aberdeen, MD 21001, USA
Ph: 800-638-7620 • Fax: 410-272-8508 Visit us online at www.harfordduracool.com

©2004 Harford 2677 - 2/04 Continuing product improvement may necessitate change of specifications without notice.

